

Safety Data Sheet acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

1 Identification

- **Product identifier**
- **Trade name:** IMP196 Clear Coat - UV Stable
- **Article number:** IMP196
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Manufactured for Refinish Distributors Alliance
PO Box 10431 Jackson, TN 38308
- **Information department:** 731 394 9366 Refinish Distributor Alliance www.impactcollisionsolutions.com
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS04 GHS07

- **Signal word** Danger
- **Hazard-determining components of labeling:**
butanone
ACRYLIC RESIN
acetone

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: IMP196 Clear Coat - UV Stable

(Contd. of page 1)

2,6-dimethylheptan-4-one

Hazard statements
H222-H229 *Extremely flammable aerosol. Pressurized container: May burst if heated.*H315 *Causes skin irritation.*H319 *Causes serious eye irritation.*H317 *May cause an allergic skin reaction.*H335-H336 *May cause respiratory irritation. May cause drowsiness or dizziness.*
Precautionary statements
P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*P251 *Pressurized container: Do not pierce or burn, even after use.*P211 *Do not spray on an open flame or other ignition source.*P261 *Avoid breathing dust/fume/gas/mist/vapors/spray*P280 *Wear protective gloves.*P280 *Wear eye protection / face protection.*P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*P321 *Specific treatment (see on this label).*P304+P340 *IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*P312 *Call a poison center/doctor if you feel unwell.*P363 *Wash contaminated clothing before reuse.*P405 *Store locked up.*P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*
Classification system:
NFPA ratings (scale 0 - 4)


Health = 1

Fire = 4

Reactivity = 3

HMIS-ratings (scale 0 - 4)

HEALTH	1
FIRE	4
REACTIVITY	3

Health = 1

Fire = 4

Reactivity = 3

Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures
Description:
Mixture: consisting of the following components.
Weight percentages
Dangerous components:

115-10-6	dimethyl ether	30 - 40%
----------	----------------	----------

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: IMP196 Clear Coat - UV Stable

(Contd. of page 2)

110-19-0	isobutyl acetate	13 - 30%
78-93-3	butanone	13 - 30%
	ACRYLIC RESIN	13 - 30%
67-64-1	acetone	10 -13%
108-83-8	2,6-dimethylheptan-4-one	1.5 - 5%
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate	1.5 - 5%
19549-80-5	4,6-dimethylheptan-2-one	1-1.5%
25973-55-1	2-(2-HYDROXY-3-5-DI--(TERT)-AMYLPHENYL)BENZOTRIAZOLE	≤1%
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidiny)l sebacate	≤1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: **IMP196 Clear Coat - UV Stable**

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not gas tight seal receptacle.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEEL	Long-term value: 1000 ppm
------	---------------------------

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m ³ , 150 ppm
-----	--

REL	Long-term value: 700 mg/m ³ , 150 ppm
-----	--

TLV	Long-term value: 713 mg/m ³ , 150 ppm
-----	--

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
-----	--

REL	Short-term value: 885 mg/m ³ , 300 ppm
-----	---

	Long-term value: 590 mg/m ³ , 200 ppm
--	--

TLV	Short-term value: 885 mg/m ³ , 300 ppm
-----	---

	Long-term value: 590 mg/m ³ , 200 ppm
--	--

	BEI
--	-----

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
-----	--

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: IMP196 Clear Coat - UV Stable

(Contd. of page 4)

REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI
108-83-8 2,6-dimethylheptan-4-one	
PEL	Long-term value: 290 mg/m ³ , 50 ppm
REL	Long-term value: 150 mg/m ³ , 25 ppm
TLV	Long-term value: 145 mg/m ³ , 25 ppm
· Ingredients with biological limit values:	
78-93-3 butanone	
BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK
67-64-1 acetone	
BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: IMP196 Clear Coat - UV Stable

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Aerosol
· Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	-24 °C

· Flash point: -42 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 235 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

· Lower:	1.8 Vol %
· Upper:	18.6 Vol %

· Vapor pressure at 20 °C: 5200 hPa

· Density at 20 °C: 0.78763 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

· Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· Solvent content:

· Organic solvents: 84.1 %

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: IMP196 Clear Coat - UV Stable

(Contd. of page 6)

VOC content: 71.9 %
645.0 g/l / 5.38 lb/gl

Solids content: 15.8 %
· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: IMP196 Clear Coat - UV Stable

(Contd. of page 7)

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
 - **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **Transport hazard class(es)**
- **DOT**
-
- **Class** 2.1
- **Label** 2.1

- **ADR**
-
- **Class** 2 5F Gases
- **Label** 2.1

- **IMDG, IATA**
-
- **Class** 2.1
- **Label** 2.1

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: **IMP196 Clear Coat - UV Stable**

(Contd. of page 8)

· Packing group · DOT, ADR, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number:	Warning: Gases F-D,S-U
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· ADR · Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, Aerosols, 2.1

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

78-93-3	butanone
1330-20-7	xylene
100-41-4	ethylbenzene

· TSCA (Toxic Substances Control Act):

115-10-6	dimethyl ether
110-19-0	isobutyl acetate
78-93-3	butanone
67-64-1	acetone
108-83-8	2,6-dimethylheptan-4-one
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
19549-80-5	4,6-dimethylheptan-2-one
25973-55-1	2-(2-HYDROXY-3-5-DI--(TERT)-AMYLPHENYL)BENZOTRIAZOLE
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: IMP196 Clear Coat - UV Stable

(Contd. of page 9)

1330-20-7	xylene
122-99-6	2-Phenoxyethanol
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
100-41-4	ethylbenzene
106-79-6	Dimethyl sebacate(Impurity)
104-68-7	Diethylene glycol monophenyl ether

· Proposition 65
· Chemicals known to cause cancer:

1330-20-7	xylene
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories
· EPA (Environmental Protection Agency)

78-93-3	butanone	I
67-64-1	acetone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)

67-64-1	acetone	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms


GHS02 GHS04 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

butanone
 ACRYLIC RESIN
 acetone
 2,6-dimethylheptan-4-one

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.
 H315 Causes skin irritation.

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2015

Reviewed on 05/29/2015

Trade name: IMP196 Clear Coat - UV Stable

(Contd. of page 10)

- H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
- **Precautionary statements**
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P211 Do not spray on an open flame or other ignition source.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P280 Wear protective gloves.
 P280 Wear eye protection / face protection.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P321 Specific treatment (see on this label).
 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312 Call a poison center/doctor if you feel unwell.
 P363 Wash contaminated clothing before reuse.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** RDA Safety Department 731 394 9366
- **Date of preparation / last revision** 05/29/2015 / 6
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - ACGIH: American Conference of Governmental Industrial Hygienists
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
 - Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 - Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
 - Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
 - STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- *** Data compared to the previous version altered.**