



TECHNICAL DATA SHEET

IMP196 UV Stable Clear Coat

IMP196 UV STABLE CLEAR COAT is an aerosol clear for quick gloss over automotive basecoat.

FEATURES

- › Convenient aerosol saves mixing time
- › Fast dry time improves efficiency
- › Excellent spray and atomization
- › Excellent gloss and color holdout
- › UV resistant

PROPERTIES

- › IMP196 UV Stable Clear Coat Aerosol Container
- › MIR: Category CCP<1.5
- › Covers 28.6 square feet at 1 mil DFT

SUITABLE SURFACES

- › Basecoat

APPLICATION & HANDLING

- › Shake well before using
- › Allow basecoat to flash according to manufacturer's instructions
- › Apply 3 medium coats
- › Maintain 6 to 8 inches distance when spraying
- › Flash time is 5 minutes between coats
- › Allow IMP196 UV Stable Clear Coat at least 1 hour drying time before handling

NOTES

- › If an excess of IMP196 UV Stable Clear Coat is applied, or if it is applied prior to the basecoat having flashed off properly, re-wetting of the basecoat may occur.
- › When not in use, orient can upside down and spray for a few seconds to clear the spray tip.

STORAGE

- › IMP196 UV Stable Clear Coat should be stored in a cool, dry location with adequate ventilation. Store away from any heat, flames or any area where sparks may be present. Shelf life is 5 years when stored properly and under normal conditions.

Disclaimer: The information provided in this technical data sheet is for guidance only. The technical data sheet is not a warranty. All implied warranties are expressly disclaimed. Users of IMP196 UV Stable Clear Coat are responsible for the product. Be sure it is suitable for your environment and needs. All data is subject to change. Always review the Safety Data Sheet (SDS) and product label to determine health hazards, usage instructions and precautions. SDS and product label are available upon request.

Check local VOC regulations to ensure compliance in your area.

IMPACT Performance Products are distributed by members of **Refinish Distributors Alliance, Inc.**

P.O. Box 10431, Jackson, TN 38308, (731) 394-9366

www.rda-impact.com