



TECHNICAL DATA SHEET

IMP199 Adhesion Promoter

IMP199 Adhesion Promoter allows proper adhesion of top coat material to olefin based plastics.

FEATURES

- ›Excellent on olefin-based plastics
- ›Topcoat with most refinish products
- ›Superior bonding properties
- ›Easy to apply aerosol can

PROPERTIES

- ›IMP199 Adhesion Promoter Aerosol Container
- ›MIR: Category ABT < 1.75

SUITABLE SURFACES

- ›Olefin-based plastics

APPLICATION & HANDLING

- ›Clean area with soap and sand with a gray scuff pad or 400 grit paper.
- ›Rinse with water and allow to dry.
- ›Clean with a wax and grease remover that is suitable for plastics.
- ›Apply one light coat.
- ›Allow 5 minutes flash time followed by one full wet coat.
- ›Allow to flash 15 minutes but no longer than 30 minutes before topcoating.
- ›Refinish with base coats, clear coats, urethanes, acrylic enamels, alkyd enamels and acrylic lacquers.

NOTES

- ›After each use, turn can upside down and spray several seconds to clear spray tip.

STORAGE

- ›IMP199 Adhesion Promoter should be stored in a cool, dry location with adequate ventilation. Store away from any heat, flames or any area where sparks may be present. Shelf life is 5 years when stored properly and under normal conditions.

Disclaimer: The information provided in this technical data sheet is for guidance only. The technical data sheet is not a warranty. All implied warranties are expressly disclaimed. Users of IMP199 Adhesion Promoter are responsible for the product. Be sure it is suitable for your environment and needs. All data is subject to change. Always review the Safety Data Sheet (SDS) and product label to determine health hazards, usage instructions and precautions. SDS and product label are available upon request.

Check local VOC regulations to ensure compliance in your area.

IMPACT Performance Products are distributed by members of **Refinish Distributors Alliance, Inc.**

P.O. Box 10431, Jackson, TN 38308, (731) 394-9366

www.rda-impact.com