TECHNICAL DATA SHEET
IMP202 Trim Black

IMP202 Trim Black is a coating that easily restores faded and peeling trim parts

FEATURES
❱Maximum adhesion and flexibility
❱No primer needed
❱Smooth, consistent finish

PROPERTIES
❱IMP202 Trim Black Aerosol Container
❱MIR Category ABT < 1.75

SUITABLE SURFACES
❱Aluminum
❱Chrome
❱Plastic
❱Stainless Steel
❱Steel

RELATED PRODUCTS
❱IMP199 Adhesion Promoter

APPLICATION & HANDLING
❱ALUMINUM, STEEL, STAINLESS STEEL AND CHROME: Clean surface with a wax and grease remover. Sand surface with 400 grit sand paper. Re-clean with a wax and grease remover.
❱PLASTIC: Clean thoroughly with a wax and grease remover. To promote adhesion on TPO, EPDM, PP and other similar thermoplastics, use IMP199 Adhesion Promoter.
❱Shake can for one minute after mixing ball rattles to ensure color uniformity and to prevent clogging.
❱Apply 2-3 medium wet coats.
❱Allow 3-5 minutes flash time between coats.

NOTES
❱After each use, turn can upside down and spray several seconds to clear spray tip.

STORAGE
❱IMP202 Trim Black should be stored in a cool, dry location with adequate ventilation. Store away from any heat, flames or any area where sparks may be present. Shelf life is 5 years when stored properly and under normal conditions.

Check local VOC regulations to ensure compliance in your area.