



# TECHNICAL DATA SHEET

## IMP232 Black Guide Coat

**IMP232 Black Guide Coat is an aerosol coating used to identify surface imperfections prior to sanding primer.**

### FEATURES

- › Won't clog sandpaper
- › Improves production
- › Dries fast

### PROPERTIES

- › IMP232 Black Guide Coat Aerosol Container
- › MIR Category ABP < 1.55

### SUITABLE SURFACES

- Primer

### APPLICATION & HANDLING

- › Complete repair per manufacturer's instructions.
- › Shake can for one minute after mixing ball rattles to prevent clogging.
- › Apply a light coat over the area. Sand until Black Guide Coat can no longer be seen.

### NOTES

- › After each use, turn can upside down and spray several seconds to clear spray tip.

### STORAGE

- › IMP232 Black Guide Coat should be stored in a cool, dry location with adequate ventilation. Store away from any heat, flames or any areas where sparks may be present. Shelf life is 3 years when stored properly and under normal conditions.

Disclaimer: The information provided in this technical data sheet is for guidance only. The technical data sheet is not a warranty. All implied warranties are expressly disclaimed. Users of IMP232 Black Guide Coat are responsible for the product. Be sure it is suitable for your environment and needs. All data is subject to change. Always review the Safety Data Sheet (SDS) and product label to determine health hazards, usage instructions and precautions. SDS and product label are available upon request.

Check local VOC regulations to ensure compliance in your area.

*IMPACT Performance Products are distributed by members of* **Refinish Distributors Alliance, Inc.**

P.O. Box 10431, Jackson, TN 38308, (731) 394-9366

[www.rda-impact.com](http://www.rda-impact.com)