

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

* 1 Identification

- **Product identifier**
- **Trade name: IMP5600 High Solids Clearcoat**
- **Article number: IMP5600**
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Manufactured for Refinish Distributors Alliance
PO Box 10431 Jackson, TN 38308
- **Information department:** 731 394 9366 Refinish Distributor Alliance www.impactcollisionsolutions.com
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)
USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: **IMP5600 High Solids Clearcoat**

(Contd. of page 1)

· **Hazard pictograms**· **Signal word** *Danger*· **Hazard-determining components of labeling:**

4-methylpentan-2-one
 n-butyl acetate
 acetone
 4-chloro-alpha,alpha,alpha-trifluorotoluene

· **Hazard statements**

H225 *Highly flammable liquid and vapor.*
 H319 *Causes serious eye irritation.*
 H317 *May cause an allergic skin reaction.*
 H351 *Suspected of causing cancer.*
 H361 *Suspected of damaging fertility or the unborn child.*
 H336 *May cause drowsiness or dizziness.*

· **Precautionary statements**

P210 *Keep away from heat/sparks/open flames/hot surfaces. No smoking.*
 P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*
 P261 *Avoid breathing dust/fume/gas/mist/vapors/spray*
 P280 *Wear protective gloves / eye protection / face protection.*
 P240 *Ground/bond container and receiving equipment.*
 P242 *Use only non-sparking tools.*
 P243 *Take precautionary measures against static discharge.*
 P264 *Wash thoroughly after handling.*
 P271 *Use only outdoors or in a well-ventilated area.*
 P272 *Contaminated work clothing must not be allowed out of the workplace.*
 P201 *Obtain special instructions before use.*
 P202 *Do not handle until all safety precautions have been read and understood.*
 P303+P361+P353 *If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
 P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
 P321 *Specific treatment (see on this label).*
 P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
 P312 *Call a POISON CENTER/doctor if you feel unwell.*
 P363 *Wash contaminated clothing before reuse.*
 P308+P313 *IF exposed or concerned: Get medical advice/attention.*
 P333+P313 *If skin irritation or rash occurs: Get medical advice/attention.*
 P337+P313 *If eye irritation persists: Get medical advice/attention.*
 P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.*
 P405 *Store locked up.*
 P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
 P403+P235 *Store in a well-ventilated place. Keep cool.*
 P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)
USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016


Trade name: **IMP5600 High Solids Clearcoat**

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

- **Dangerous components:**

123-86-4 n-butyl acetate	13 - 30%
67-64-1 acetone	13 - 30%
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene	7 - 10%
108-10-1 4-methylpentan-2-one	7 - 10%
110-19-0 isobutyl acetate	7 - 10%
590-01-2 n-butyl propionate	1.5 - 5%
763-69-9 ethyl 3-ethoxypropionate	1.5 - 5%
108-83-8 2,6-dimethylheptan-4-one	1-1.5%
108-88-3 toluene	≤1%
41556-26-7 bis(1,2,2,6,6-Pentamethyl-4-piperidiny)l) sebacate	≤1%
100-41-4 ethylbenzene	≤1%

* 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)
USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: IMP5600 High Solids Clearcoat

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.

(Contd. on page 5)
USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: IMP5600 High Solids Clearcoat

(Contd. of page 4)

Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm
 Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 712 mg/m³, 150 ppm
 Long-term value: 238 mg/m³, 50 ppm

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm
 Long-term value: 594 mg/m³, 250 ppm
 BEI

108-10-1 4-methylpentan-2-one

PEL Long-term value: 410 mg/m³, 100 ppm

REL Short-term value: 300 mg/m³, 75 ppm
 Long-term value: 205 mg/m³, 50 ppm

TLV Short-term value: 307 mg/m³, 75 ppm
 Long-term value: 82 mg/m³, 20 ppm
 BEI

110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m³, 150 ppm

REL Long-term value: 700 mg/m³, 150 ppm

TLV Short-term value: 172 mg/m³, 150 ppm
 Long-term value: 238 mg/m³, 50 ppm

108-83-8 2,6-dimethylheptan-4-one

PEL Long-term value: 290 mg/m³, 50 ppm

REL Long-term value: 150 mg/m³, 25 ppm

TLV Long-term value: 145 mg/m³, 25 ppm

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: IMP5600 High Solids Clearcoat

(Contd. of page 5)

REL Short-term value: 560 mg/m³, 150 ppmLong-term value: 375 mg/m³, 100 ppmTLV Long-term value: 75 mg/m³, 20 ppm

BEI

100-41-4 ethylbenzenePEL Long-term value: 435 mg/m³, 100 ppmREL Short-term value: 545 mg/m³, 125 ppmLong-term value: 435 mg/m³, 100 ppmTLV Long-term value: 87 mg/m³, 20 ppm

BEI

Ingredients with biological limit values:**67-64-1 acetone**

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

108-10-1 4-methylpentan-2-one

BEI 1 mg/L

Medium: urine

Time: end of shift

Parameter: MIBK

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L

Medium: urine

Time: end of shift

Parameter: Toluene

0.3 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: **IMP5600 High Solids Clearcoat**

(Contd. of page 6)

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

* 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:

Liquid

Color:

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: **IMP5600 High Solids Clearcoat**

(Contd. of page 7)

· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C
· Flash point:	-18 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C:	233 hPa
· Density at 20 °C:	0.96322 g/cm ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	67.7 %
VOC content:	42.0 %
	549.4 g/l / 4.58 lb/gl
Solids content:	32.1 %
· Other information	No further relevant information available.

*10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA
(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: **IMP5600 High Solids Clearcoat**

(Contd. of page 8)

*11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-10-1 4-methylpentan-2-one

2B

108-88-3 toluene

3

1330-20-7 xylene

3

100-41-4 ethylbenzene

2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

*12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: **IMP5600 High Solids Clearcoat**

(Contd. of page 9)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

*14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** 1263 Paint, special provision 640D
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**



- **Class** 3 Flammable liquids
- **Label** 3
- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** II
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Flammable liquids
- **EMS Number:** F-E, S-E
- **Stowage Category** B
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

(Contd. on page 11)
USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: **IMP5600 High Solids Clearcoat**

(Contd. of page 10)

- **ADR**
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":** UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.
- **Section 313 (Specific toxic chemical listings):**
 - 108-10-1 4-methylpentan-2-one
 - 108-88-3 toluene
 - 1330-20-7 xylene
 - 122-99-6 2-Phenoxyethanol
 - 100-41-4 ethylbenzene
 - 104-68-7 Diethylene glycol monophenyl ether
- **TSCA (Toxic Substances Control Act):**
 - 123-86-4 n-butyl acetate
 - 67-64-1 acetone
 - 98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene
 - 108-10-1 4-methylpentan-2-one
 - 110-19-0 isobutyl acetate
 - 590-01-2 n-butyl propionate
 - 763-69-9 ethyl 3-ethoxypropionate
 - 108-83-8 2,6-dimethylheptan-4-one
 - 108-88-3 toluene
 - 1330-20-7 xylene
 - UV Absorber
 - 19549-80-5 4,6-dimethylheptan-2-one
 - 41556-26-7 bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate
 - 122-99-6 2-Phenoxyethanol
 - 100-41-4 ethylbenzene

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: IMP5600 High Solids Clearcoat

(Contd. of page 11)

- **Proposition 65**

- **Chemicals known to cause cancer:**

- 108-10-1 4-methylpentan-2-one

- 1330-20-7 xylene

- 100-41-4 ethylbenzene

- **Chemicals known to cause reproductive toxicity for females:**

- None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

- None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

- 108-10-1 4-methylpentan-2-one

- 108-88-3 toluene

- **Carcinogenicity categories**

- **EPA (Environmental Protection Agency)**

- 67-64-1 acetone

I

- 108-10-1 4-methylpentan-2-one

I

- 108-88-3 toluene

II

- 1330-20-7 xylene

I

- 100-41-4 ethylbenzene

D

- **TLV (Threshold Limit Value established by ACGIH)**

- 67-64-1 acetone

A4

- 108-88-3 toluene

A4

- 1330-20-7 xylene

A4

- 100-41-4 ethylbenzene

A3

- 77-58-7 dibutyltin dilaurate

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

- None of the ingredients is listed.

- **GHS label elements**

- The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02

GHS07

GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

- 4-methylpentan-2-one

- n-butyl acetate

- acetone

- 4-chloro-alpha,alpha,alpha-trifluorotoluene

- **Hazard statements**

- H225 Highly flammable liquid and vapor.

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: IMP5600 High Solids Clearcoat

(Contd. of page 12)

- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.

- **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves / eye protection / face protection.
- P240 Ground/bond container and receiving equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P321 Specific treatment (see on this label).
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P363 Wash contaminated clothing before reuse.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P405 Store locked up.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** RDA Safety Department 731 394 9366

- **Date of preparation / last revision** 10/06/2016 / 10

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 14)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/06/2016

Reviewed on 10/06/2016

Trade name: IMP5600 High Solids Clearcoat

(Contd. of page 13)

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• *** Data compared to the previous version altered.**

USA