

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

1 Identification

- **Product identifier**
- **Trade name:** IMP6500 Clear Coat Euro Style 2:1
- **Article number:** IMP6500
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Manufactured for Refinish Distributors Alliance
PO Box 10431 Jackson, TN 38308
- **Information department:** 731 394 9366 Refinish Distributor Alliance www.impactcollisionsolutions.com
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: IMP6500 Clear Coat Euro Style 2:1

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

4-methylpentan-2-one

acetone

n-butyl acetate

4-chloro-alpha,alpha,alpha-trifluorotoluene

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1
FIRE	3
REACTIVITY	0

Health = 1

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: IMP6500 Clear Coat Euro Style 2:1

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture consisting of the following components.
Weight percentages

- **Dangerous components:**

	ACRYLIC RESIN	40 - 60%
67-64-1	acetone	13 - 30%
123-86-4	n-butyl acetate	13 - 30%
1330-20-7	xylene	5 - 7%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	5 - 7%
110-43-0	heptan-2-one	1.5 - 5%
108-10-1	4-methylpentan-2-one	1.5 - 5%
25973-55-1	2-(2-HYDROXY-3-5-DI--(TERT)-AMYLPHENYL)BENZOTRIAZOLE	1-1.5%
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate	≤1%
100-41-4	ethylbenzene	≤1%
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidiny) sebacate	≤1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: IMP6500 Clear Coat Euro Style 2:1

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm
	Long-term value: 594 mg/m ³ , 250 ppm
BEI	

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m ³ , (200) NIC-150 ppm
	Long-term value: (713) NIC-238 mg/m ³ , (150) NIC-50 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: IMP6500 Clear Coat Euro Style 2:1

(Contd. of page 4)

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

108-10-1 4-methylpentan-2-one

PEL Long-term value: 410 mg/m³, 100 ppm

REL Short-term value: 300 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm

TLV Short-term value: 307 mg/m³, 75 ppm
Long-term value: 82 mg/m³, 20 ppm
BEI

· Ingredients with biological limit values:**67-64-1 acetone**

BEI 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

108-10-1 4-methylpentan-2-one

BEI 1 mg/L
Medium: urine
Time: end of shift
Parameter: MIBK

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: IMP6500 Clear Coat Euro Style 2:1

(Contd. of page 5)

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid
Color: According to product specification

· **Odor:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 55 °C

· **Flash point:** -18 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 1.2 Vol %
Upper: 13.0 Vol %

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: IMP6500 Clear Coat Euro Style 2:1

(Contd. of page 6)

· Vapor pressure at 20 °C:	233 hPa
· Density at 20 °C:	0.96783 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	54.2 %
VOC content:	31.9 %
	409.5 g/l / 3.42 lb/gl
· Solids content:	45.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

1330-20-7	xylene	3
108-10-1	4-methylpentan-2-one	2B
100-41-4	ethylbenzene	2B

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: IMP6500 Clear Coat Euro Style 2:1

(Contd. of page 7)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
*Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | <p>UN1263</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA | <p>Paint
 1263 Paint, special provision 640D
 PAINT</p> |

(Contd. on page 9)

-USA-

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: *IMP6500 Clear Coat Euro Style 2:1*

(Contd. of page 8)

· **Transport hazard class(es)**· **DOT**

· **Class** 3 Flammable liquids
 · **Label** 3

· **ADR, IMDG, IATA**

· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**· **DOT, ADR, IMDG, IATA** II· **Environmental hazards:**· **Marine pollutant:** No· **Special precautions for user** Warning: Flammable liquids· **EMS Number:** F-E,S-E

· **Transport in bulk according to Annex II of
 MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· **ADR**

· **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN1263, Paint, special provision 640D, 3, II

USA

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: **IMP6500 Clear Coat Euro Style 2:1**

(Contd. of page 9)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

	ACRYLIC RESIN
1330-20-7	xylene
108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone
123-86-4	n-butyl acetate
1330-20-7	xylene
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
110-43-0	heptan-2-one
108-10-1	4-methylpentan-2-one
25973-55-1	2-(2-HYDROXY-3-5-DI--(TERT)-AMYLPHENYL)BENZOTRIAZOLE
64742-95-6	Solvent naphtha (petroleum), light arom.
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate
122-99-6	2-Phenoxyethanol
100-41-4	ethylbenzene
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
77-58-7	dibutyltin dilaurate
104-68-7	Diethylene glycol monophenyl ether
106-79-6	Dimethyl sebacate(Impurity)

· **Proposition 65**

· **Chemicals known to cause cancer:**

1330-20-7	xylene
108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-10-1	4-methylpentan-2-one
----------	----------------------

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: IMP6500 Clear Coat Euro Style 2:1

(Contd. of page 10)

108-10-1	4-methylpentan-2-one	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
77-58-7	dibutyltin dilaurate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

4-methylpentan-2-one

acetone

n-butyl acetate

4-chloro-alpha,alpha,alpha-trifluorotoluene

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/19/2015

Reviewed on 06/19/2015

Trade name: IMP6500 Clear Coat Euro Style 2:1

(Contd. of page 11)

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** RDA Safety Department 731 394 9366

· **Date of preparation / last revision** 06/19/2015 / 6

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· *** Data compared to the previous version altered.**

USA