



Printing date 06/19/2015 Reviewed on 06/17/2015

1 Identification

- · Product identifier
- · Trade name: IMP6575 Medium Activator Euro Style 2:1
- · Article number: IMP6575
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Coating

Isocyanate Hardener

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufactured for Refinish Distributors Alliance

PO Box 10431 Jackson, TN 38308

- · Information department: 731 394 9366 Refinish Distributor Alliance www.impactcollisionsolutions.com
- · Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



 $GHS02\ Flame$

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 2 H371-H335 May cause damage to organs. May cause respiratory irritation.



GHS07

Acute Tox. 4	H302	Harmful if swallowed.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)

. on page 2)

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

(Contd. of page 1)

· Hazard pictograms







GHS07

· Signal word Danger

· Hazard-determining components of labeling:

HDI Prepolymer heptan-2-one 4-methylpentan-2-one

2-butoxyethyl acetate · Hazard statements

Highly flammable liquid and vapor. H225 H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H371-H335 May cause damage to organs. May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P284 Wear respiratory protection.

P280 Wear protective gloves / eye protection / face protection. P240 Ground/bond container and receiving equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P342+P311 *If experiencing respiratory symptoms: Call a poison center/doctor.* If swallowed: Call a poison center/doctor if you feel unwell. P301+P312

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for P304+P340

breathing.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1Fire = 3Reactivity = 0

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

· HMIS-ratings (scale 0 - 4)

HEALTH *1 Health = *1FIRE 3 Fire = 3REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	· Dangerous components:		
28182-81-2	HDI Prepolymer	30 - 40%	
110-43-0	heptan-2-one	13 - 30%	
	4-methylpentan-2-one	10 -13%	
	n-butyl acetate	10 -13%	
	2-butoxyethyl acetate	7 - 10%	
	2,6-dimethylheptan-4-one	5 - 7%	
19549-80-5	4,6-dimethylheptan-2-one	1.5 - 5%	

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textit{Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

(Contd. on page 4)

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

(Contd. of page 3)

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

(Contd. on page 5)

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

	(Contd. of page 4)
TLV	Long-term value: 233 mg/m³, 50 ppm
108-	10-1 4-methylpentan-2-one
PEL	Long-term value: 410 mg/m³, 100 ppm
REL	Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm
TLV	Short-term value: 307 mg/m³, 75 ppm Long-term value: 82 mg/m³, 20 ppm BEI
123-	86-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m^3 , 200 ppm Long-term value: 710 mg/m^3 , 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm
112-	07-2 2-butoxyethyl acetate
REL	Long-term value: 33 mg/m³, 5 ppm
TLV	Long-term value: 130 mg/m³, 20 ppm
108-	83-8 2,6-dimethylheptan-4-one
PEL	Long-term value: 290 mg/m³, 50 ppm
REL	Long-term value: 150 mg/m³, 25 ppm
TLV	Long-term value: 145 mg/m³, 25 ppm
· Ingr	edients with biological limit values:
108-	10-1 4-methylpentan-2-one
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
Addi	tional information: The lists that were valid during the creation were used as basis

- \cdot Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



(Contd. on page 6)

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Informat	ion on basic physical and chemical properties
· General I	Information
· Appearan	nce:

Form: Liquid

Color: According to product specification

· Odor: Characteristic · Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: 114 °C

14 °C · Flash point:

· Flammability (solid, gaseous): Not applicable.

280 °C · Ignition temperature:

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower: 1.0 Vol % 9.0 Vol % Upper:

· Vapor pressure at 20 °C: 10.7 hPa

· Density at 20 °C: 0.92713 g/cm3 · Relative density Not determined.

· Vapour density Not determined. · Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

(Contd. on page 7)

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

		(Contd. of page
Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	62.5 %	
VOC content:	62.5 %	
	579.9 g/l / 4.84 lb/gl	
Solids content:	37.4 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:		
28182-81-2	28182-81-2 HDI Prepolymer		
Oral	LD50	1000 mg/kg (rat)	
Dermal	LD50	5000 mg/kg (rabbit)	
Inhalative	LC50/4 h	137-1150 mg/l (rat)	
110-43-0 h	110-43-0 heptan-2-one		
Oral	LD50	1670 mg/kg (rat)	
Dermal	LD50	12600 mg/kg (rabbit)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

(Contd. on page 8)

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

(Contd. of page 7)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

108-10-1 4-methylpentan-2-one

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1993
· DOI, ADK, IMDG, IATA	UN1993
· UN proper shipping name	
$\cdot DOT$	Flammable liquids, n.o.s. (Methyl isobutyl ketone, n-Amyl methy
	ketone)
· ADR	1993 Flammable liquids, n.o.s. (Methyl isobutyl ketone, n-Amy
	methyl ketone), special provision 640D

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

	(Contd. of page 8)
· IMDG · IATA	FLAMMABLE LIQUID, N.O.S. (METHYL ISOBUTYL KETONE, n-AMYL METHYL KETONE, HDI Prepolymer) FLAMMABLE LIQUID, N.O.S. (METHYL ISOBUTYL KETONE, n-
	AMYL METHYL KETONE)
· Transport hazard class(es)	
· DOT	
· Class · Label	3 Flammable liquids 3
· ADR, IMDG	
· Class · Label	3 Flammable liquids 3
· IATA	
· Class · Label	3 Flammable liquids 3
· Packing group · DOT, ADR, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: HDI
· Marine pollutant:	Prepolymer Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user · EMS Number:	Warning: Flammable liquids F-E, <u>S-E</u>
· Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	T of Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
	(Contd. on page 10)

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

	(Contd. of page 9
· ADR	
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
\cdot IMDG	
· Limited quantities (LQ)	IL
\cdot Excepted quantities (EQ)	Code: E2
• • • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN1993, Flammable liquids, n.o.s. (Methyl isobutyl ketone, n-Amymethyl ketone), special provision 640D, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-10-1 4-methylpentan-2-one

112-07-2 2-butoxyethyl acetate

- · TSCA (Toxic Substances Control Act):
- All ingredients are listed.
- · Proposition 65
- · Chemicals known to cause cancer:

108-10-1 4-methylpentan-2-one

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-10-1 4-methylpentan-2-one

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

108-10-1 4-methylpentan-2-one

4.2

· TLV (Threshold Limit Value established by ACGIH)

112-07-2 2-butoxyethyl acetate

A3

Ι

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 11)

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

(Contd. of page 10)

· Hazard pictograms







GHS07

· Signal word Danger

· Hazard-determining components of labeling:

HDI Prepolymer heptan-2-one

4-methylpentan-2-one 2-butoxyethyl acetate

· Hazard statements

Highly flammable liquid and vapor. H225 H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation. H319 Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H371-H335 May cause damage to organs. May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P284 Wear respiratory protection.

P280 Wear protective gloves / eye protection / face protection. P240 Ground/bond container and receiving equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P342+P311 *If experiencing respiratory symptoms: Call a poison center/doctor.* P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: RDA Safety Department 731 394 9366
- · Date of preparation / last revision 06/19/2015 / 7

(Contd. on page 12)

Printing date 06/19/2015 Reviewed on 06/17/2015

Trade name: IMP6575 Medium Activator Euro Style 2:1

(Contd. of page 11)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2

* Data compared to the previous version altered.

USA